



## **Veřejné osvětlení, reflektory, svítidla do průmyslových hal**

### **Ceník**

Záruka 5let

Ceny lze individuálně upravit podle výše odběru.

Kontaktní údaje: LED-LUMIN s.r.o.  
Vodňanská 664  
Praha 9 - Kyje  
198 00




[www.ledlumin.cz](http://www.ledlumin.cz), [obchod@ledlumin.cz](mailto:obchod@ledlumin.cz), 774 372 045

Společnost LED-LUMIN s.r.o. si vyhrazuje právo na změnu cen.

**Veřejné osvětlení**

Typ	Model	Specifikace	Cena bez DPH	
	RT510SL			
	RT510SL10W/(AC/DC)	Power : 10w-30w Power Factor (PF) : > 0.9 LED Luminous Efficiency: 130lm/W Operating Voltage: DC(12V 24V) AC(100V~277V)/Frequency(50~60Hz) Efficiency: > 90% Effective Beam Angle: 130° Ra) 75 color temperature : 2700K~7000K Light Source Life-span: > 50000Hrs Protection class IP65 Net weight (Unit: kg): 2.5kg	3 247,20 Kč	
	RT510SL20W/(AC/DC)		3 387,60 Kč	
	RT510SL25W/(AC/DC)		3 528,00 Kč	
		RT530SL		
		RT530SL10W/(AC/DC)	Power : 10w-40w Power Factor (PF) : > 0.9 LED Luminous Efficiency: 130lm/W Operating Voltage: DC(12V 24V) AC(100V~277V)/Frequency(50~60Hz) Efficiency: > 90% Effective Beam Angle: 130° Ra) 75 color temperature : 2700K~7000K Light Source Life-span: > 50000Hrs Protection class IP65 Net weight (Unit: kg): 4kg	4 370,40 Kč
		RT530SL20W/(AC/DC)		4 557,60 Kč
		RT530SL30W/(AC/DC)		4 768,20 Kč
		RT570SL		
		RT570SL10W/(AC/DC)	Power : 10w-70w Power Factor (PF) : > 0.9 LED Luminous Efficiency: 130lm/W Operating Voltage: DC(12V 24V) AC(100V~277V)/Frequency(50~60Hz) Efficiency: > 90% Effective Beam Angle: 130° Ra) 75 color temperature : 2700K~7000K Light Source Life-span: > 50000Hrs Protection class IP65 Net weight (Unit: kg): 5-7kg	5 236,20 Kč
		RT570SL20W/(AC/DC)		5 446,80 Kč
		RT570SL30W/(AC/DC)		5 634,00 Kč
		RT570SL40W/(AC/DC)		5 821,20 Kč
		RT570SL-H 50W/(AC/DC)		8 114,40 Kč
		RT570SL-H 60W/(AC/DC)		8 254,80 Kč
RT570SL-H 70W/(AC/DC)		8 395,20 Kč		
	RT650SL-T			
	RT650SL-T40W/(AC/DC)		9 003,60 Kč	
	RT650SL-T50W/(AC/DC)		9 518,40 Kč	
	RT650SL-T60W/(AC/DC)		9 612,00 Kč	
	RT650SL-T70W/(AC/DC)		9 658,80 Kč	
	RT650SL-T80W/(AC/DC)	Power : 40w~110w Power Factor (PF) : > 0.9 LED Luminous Efficiency: 130lm/W Operating Voltage: DC(12V 24V)/ AC(100V~277V)/Frequency(50~60Hz) Efficiency: > 90% Effective Beam Angle: 130° Ra) 75 color temperature : 2700K~7000K Light Source Life-span: > 50000Hrs Protection class IP65 Net weight (Unit: kg): 9.8kg	9 705,60 Kč	
	RT650SL-T90W/(AC/DC)		10 454,40 Kč	
	RT650SL-T100W/(AC/DC)		10 688,40 Kč	
	RT650SL-T110W/(AC/DC)		10 828,80 Kč	

Veřejné osvětlení

	<b>RT750SL-T</b>	RT750SL-T60W/(AC/DC)	Power : 60w--140w Power Factor (PF) : > 0.9 LED Luminous Efficiency: <b>130lm/W</b> Operating Voltage: DC(12V 24V)/ AC(100V~277V)/Frequency(50~60Hz) Efficiency: > 90% Effective Beam Angle: 130° Ra) 75 color temperature : 2700K~7000K Light Source Life-span: > 50000Hrs Protection class IP65 Net weight (Unit: kg): 12.95kg	12 326,40 Kč	
		RT750SL-T70W/(AC/DC)		12 420,00 Kč	
		RT750SL-T80W/(AC/DC)		12 794,40 Kč	
		RT750SL-T90W/(AC/DC)		13 122,00 Kč	
		RT750SL-T100W/(AC/DC)		13 356,00 Kč	
		RT750SL-T110W/(AC/DC)		13 590,00 Kč	
		RT750SL-T120W/(AC/DC)		13 777,20 Kč	
		RT750SL-T140W/(AC/DC)		14 292,00 Kč	
		<b>RT600SL-T</b>	RT600SL-T60W/(AC/DC)	Power : 60w--120w Power Factor (PF) : > 0.9 LED Luminous Efficiency: <b>130lm/W</b> Operating Voltage: DC(12V 24V)/ AC(100V~277V)/Frequency(50~60Hz) Efficiency: > 90% Effective Beam Angle: 130° Ra) 75 color temperature : 2700K~7000K Light Source Life-span: > 50000Hrs Protection class IP65 Net weight (Unit: kg): 12kg	12 700,80 Kč
			RT600SL-T70W/(AC/DC)		12 794,40 Kč
			RT600SL-T80W/(AC/DC)		12 981,60 Kč
			RT600SL-T90W/(AC/DC)		13 168,80 Kč
			RT600SL-T100W/(AC/DC)		13 356,00 Kč
			RT600SL-T110W/(AC/DC)		13 590,00 Kč
			RT600SL-T120W/(AC/DC)		13 730,40 Kč
		<b>RT820SL-T</b>	RT820SL-T140W/(AC/DC)	Power : 140w--200w Power Factor (PF) : > 0.9 LED Luminous Efficiency: <b>130lm/W</b> Operating Voltage: DC(12V 24V)/ AC(100V~277V)/Frequency(50~60Hz) Efficiency: > 90% Effective Beam Angle: 130° Ra) 75 color temperature : 2700K~7000K Light Source Life-span: > 50000Hrs Protection class IP65 Net weight (Unit: kg): 17kg	18 410,40 Kč
			RT820SL-T160W/(AC/DC)		19 018,80 Kč
			RT820SL-T180W/(AC/DC)		19 440,00 Kč
			RT820SL-T200W/(AC/DC)		19 954,80 Kč

Společnost LED-LUMIN s.r.o. si vyhrazuje právo na změnu cen.

**Osvětlení skladových a výrobních hal**

Typ	Model	Specifikace	Cena bez DPH
<b>RT300/400HB</b>  	RT300HB40W	Power : 40w--100w Power Factor (PF) : > 0.9 LED Luminous Efficiency: 130lm/W Operating Voltage: DC(12V 24V)/ AC(100V~277V)/Frequency(50~60Hz) Efficiency: > 90% Effective Beam Angle: 10°/20° /30°/40°/50°/80° Ra) 75 color temperature : 2700K~7000K Light Source Life-span: > 50000Hrs Protection class IP65 Net weight (Unit: kg): 10kg	6 102,00 Kč
	RT300HB50W		6 429,60 Kč
	RT300HB60W		6 570,00 Kč
	RT300HB70W		6 710,40 Kč
	RT400HB50W(AC)		10 173,60 Kč
	RT400HB60W(AC)		10 407,60 Kč
	RT400HB70W(AC)		10 548,00 Kč
	RT400HB80W(AC)		10 828,80 Kč
	RT400HB90W(AC)		11 109,60 Kč
	RT400HB100W(AC)		11 203,20 Kč
<b>RT500HB</b>  	RT500HB100W	Power : 100w--200w Power Factor (PF) : > 0.9 LED Luminous Efficiency: 130lm/W Operating Voltage: DC(12V 24V)/ AC(100V~277V)/Frequency(50~60Hz) Efficiency: > 90% Effective Beam Angle: 10°/20° /30°/40°/50°/80° Ra) 75 color temperature : 2700K~7000K Light Source Life-span: > 50000Hrs Protection class IP65 Net weight (Unit: kg): 15kg	15 274,80 Kč
	RT500HB120W		15 789,60 Kč
	RT500HB140W		15 976,80 Kč
	RT500HB160W		16 632,00 Kč
	RT500HB180W		17 334,00 Kč
	RT500HB200W		17 568,00 Kč
<b>RT520HB/RT520PC</b> <b>úzký + široký reflektor</b>  	RT520HB30w/(AC/DC)	Power : 30w--150w Power Factor (PF) : > 0.9 LED Luminous Efficiency: <b>130lm/W</b> Operating Voltage: DC(12V 24V)/ AC(100V~277V)/Frequency(50~60Hz) Efficiency: > 90% Effective Beam Angle: 30°/50°/100° Ra) 75 color temperature : 2700K~7000K Light Source Life-span: > 50000Hrs Protection class IP54 Net weight (Unit: kg): 3.9-5kg	6 570,00 Kč
	RT520HB40w/(AC/DC)		6 804,00 Kč
	RT520HB50w/(AC/DC)		7 459,20 Kč
	RT520HB60w/(AC/DC)		7 599,60 Kč
	RT520HB70w/(AC/DC)		7 833,60 Kč
	RT520HB80w/(AC/DC)		8 114,40 Kč
	RT520HB90w/(AC/DC)		8 301,60 Kč
	RT520HB100w/(AC/DC)		8 442,00 Kč
RT520HB150w/(AC/DC)	10 548,00 Kč		

Osvětlení  
skladových  
a výrobních  
hal

<p style="text-align: center;"><b>HB-M</b></p> 	<p style="text-align: center;">HB-M 70W(AC/DC)</p>	<p>Power : 70w  Power Factor (PF) : &gt; 0.9  LED Luminous Efficiency: <b>130lm/W</b>  Operating Voltage: DC(12V 24V)/  AC(100V~277V)/Frequency(50~60Hz)  Efficiency: &gt; 90% Effective  Beam Angle: 30°/50°  Ra) 75  color temperature : 2700K~7000K  Light Source Life-span: &gt; 50000Hrs  Protection class IP65  Net weight (Unit: kg): 6.5kg</p>	<p style="text-align: center;">7 927,20 Kč</p>
<p style="text-align: center;"><b>HB-2M</b></p> 	<p style="text-align: center;">HB-2M 140W(AC/DC)</p>	<p>Power : 140w  Power Factor (PF) : &gt; 0.9  LED Luminous Efficiency: 100lm/W  Operating Voltage: DC(12V 24V)/  AC(100V~277V)/Frequency(50~60Hz)  Efficiency: &gt; 90% Effective  Beam Angle: 30°/50°  Ra) 75  color temperature : 2700K~7000K  Light Source Life-span: &gt; 50000Hrs  Protection class IP65  Net weight (Unit: kg): 13kg</p>	<p style="text-align: center;">15 134,40 Kč</p>
<p style="text-align: center;"><b>HB-4M</b></p> 	<p style="text-align: center;">HB-4M 200W(AC/DC)</p>	<p>Power : 200W-280W  Power Factor (PF) : &gt; 0.9</p>	<p style="text-align: center;">27 864,00 Kč</p>
	<p style="text-align: center;">HB-4M 220W(AC/DC)</p>	<p>LED Luminous Efficiency: <b>130lm/W</b>  Operating Voltage: DC(12V 24V)/  AC(100V~277V)/Frequency(50~60Hz)</p>	<p style="text-align: center;">28 332,00 Kč</p>
	<p style="text-align: center;">HB-4M 240W(AC/DC)</p>	<p>Efficiency: &gt; 90% Effective  Beam Angle: 30°/50°  Ra) 75</p>	<p style="text-align: center;">28 893,60 Kč</p>
	<p style="text-align: center;">HB-4M 260W(AC/DC)</p>	<p>color temperature : 2700K~7000K  Light Source Life-span: &gt; 50000Hrs  Protection class IP65</p>	<p style="text-align: center;">29 502,00 Kč</p>
	<p style="text-align: center;">HB-4M 280W(AC/DC)</p>	<p>Net weight (Unit: kg): 27kg</p>	<p style="text-align: center;">30 016,80 Kč</p>

Společnost LED-LUMIN s.r.o. si vyhrazuje právo na změnu cen.

**LED reflektory**

Typ	Model	Specifikace	Cena bez DPH
<b>RT220UB</b> 	RT220UB10W/(AC/DC)	Power : 10w--40w	3 031,20 Kč
	RT220UB15W/(AC/DC)	Power Factor (PF) : > 0.9	3 171,60 Kč
	RT220UB20W/(AC/DC)	LED Luminous Efficiency: 130lm/W	3 358,80 Kč
	RT220UB30W/(AC/DC)	Operating Voltage: DC(12V 24V)/ AC(100V~277V)/Frequency(50~60Hz)	3 499,20 Kč
	RT220UB40W/(AC/DC)	Efficiency: > 90% Effective Beam Angle: 120° Ra) 75 color temperature : 2700K~7000K Light Source Life-span: > 50000Hrs Protection class IP65 Net weight (Unit: kg): 2.5kg	3 686,40 Kč
<b>RT180/300/370/420FS</b>  	RT180FS10W/(AC/DC)		2 071,80 Kč
	RT180FS20W/(AC/DC)		2 235,60 Kč
	RT300FS20W/(AC/DC)		3 405,60 Kč
	RT300FS30W/(AC/DC)	Power : 10w--100w	3 589,20 Kč
	RT300FS40W/(AC/DC)	Power Factor (PF) : > 0.9	4 744,80 Kč
	RT370FS50W/(AC/DC)	LED Luminous Efficiency: 130lm/W	5 680,80 Kč
	RT370FS60W/(AC/DC)	Operating Voltage: DC(12V 24V)/ AC(100V~277V)/Frequency(50~60Hz)	5 868,00 Kč
	RT370FS70W/(AC/DC)	Efficiency: > 90% Effective Beam Angle: 120° Ra) 75 color temperature : 2700K~7000K Light Source Life-span: > 50000Hrs Protection class IP65 Net weight (Unit: kg): 2-5.5kg	5 961,60 Kč
	RT420FS-S80W/(AC/DC)		7 693,20 Kč
	RT420FS-S90W/(AC/DC)		8 020,80 Kč
	RT420FS-S100W/(AC/DC)		8 161,20 Kč
<b>RT390FL</b> 	New RT390FL50W/(AC/DC)	Power : 50w--80w	8 442,00 Kč
	New RT390FL60W/(AC/DC)	Power Factor (PF) : > 0.9	8 535,60 Kč
	New RT390FL70W/(AC/DC)	LED Luminous Efficiency: <b>130lm/W</b>	8 676,00 Kč
	New RT390FL80W/(AC/DC)	Operating Voltage: DC(12V 24V)/ AC(100V~277V)/Frequency(50~60Hz)	9 003,60 Kč

<b>RT590FL-S</b> 	New RT590FL-S100W/(AC/DC)	Power : 100w--180w Power Factor (PF) : > 0.9	13 168,80 Kč
	New RT590FL-S120W/(AC/DC)	LED Luminous Efficiency: <b>130lm/W</b> Operating Voltage: DC(12V 24V)/ AC(100V~277V)/Frequency(50~60Hz)	13 636,80 Kč
	New RT590FL-S140W/(AC/DC)	Efficiency: > 90% Effective Beam Angle: 30° /50°/120° Ra) 75	13 824,00 Kč
	New RT590FL-S160W/(AC/DC)	color temperature : 2700K~7000K Light Source Life-span: > 50000Hrs Protection class IP65	14 526,00 Kč
	New RT590FL-S180W/(AC/DC)	Net weight (Unit: kg): 12.8kg	15 134,40 Kč
<b>RT330HB</b> 	RT330HB60W	Power : 60w--110w Power Factor (PF) : > 0.9	7 084,80 Kč
	RT330HB80W	LED Luminous Efficiency: 130lm/W Operating Voltage: DC(12V 24V)/ AC(100V~277V)/Frequency(50~60Hz)	7 506,00 Kč
	RT330HB100W	Efficiency: > 90% Effective Beam Angle: 30° /50°/80° Ra) 75	7 880,40 Kč
	RT330HB110W	color temperature : 2700K~7000K Light Source Life-span: > 50000Hrs Protection class IP65 Net weight (Unit: kg): 6kg	8 020,80 Kč
<b>RT660FL-S</b> 	RT660FL-S 200W(AC/DC)	Power : 200w--400w Power Factor (PF) : > 0.9	25 524,00 Kč
	RT660FL-S 240W(AC/DC)	LED Luminous Efficiency: <b>130lm/W</b> Operating Voltage: DC(12V 24V)/ AC(100V~277V)/Frequency(50~60Hz)	26 460,00 Kč
	RT660FL-S 280W(AC/DC)	Efficiency: > 90% Effective Beam Angle: 10° / 30° / 50°/140° Ra) 75	27 396,00 Kč
	RT660FL-S 320W(AC/DC)	color temperature : 2700K~7000K Light Source Life-span: > 50000Hrs Protection class IP65	28 800,00 Kč
	RT660FL-S 360W(AC/DC)	Net weight (Unit: kg): 20kg	29 736,00 Kč
	RT660FL-S 400W(AC/DC)		30 672,00 Kč
<b>RT410FL-S</b> 	RT410FL-S140W(AC/DC)	Power : 140w--200w Power Factor (PF) : > 0.9 LED Luminous Efficiency: <b>130lm/W</b>	10 782,00 Kč
	RT410FL-S160W(AC/DC)	Operating Voltage: DC(12V 24V)/ AC(100V~277V)/Frequency(50~60Hz) Efficiency: > 90% Effective	11 530,80 Kč
	RT410FL-S180W(AC/DC)	Beam Angle: 30° /50°/100/80-40/110-60 Ra) 75 color temperature : 2700K~7000K	11 998,80 Kč
	RT410FL-S200W(AC/DC)	Light Source Life-span: > 50000Hrs Protection class IP65 Net weight (Unit: kg): 14kg	12 654,00 Kč

Společnost LED-LUMIN s.r.o. si vyhrazuje právo na změnu cen.

**Svítlidla pro nasvícení objektů**

Type	Model	Specification	Cena bez DPH
<p><b>HB-M</b></p> 	HB-M 70W(AC/DC)	Power :50W- 70w Power Factor (PF) : > 0.9 LED Luminous Efficiency: <b>130lm/W</b> Operating Voltage: DC(12V 24V)/ AC(100V~277V)/Frequency(50~60Hz) Efficiency: > 90% Effective Beam Angle: 30°/50° Ra) 75 color temperature : 2700K~7000K Light Source Life-span: > 50000Hrs Protection class IP65 Net weight (Unit: kg): 6.5kg	7 927,20 Kč
<p><b>HB-2M</b></p> 	HB-2M 140W(AC/DC)	Power : 100W-140w Power Factor (PF) : > 0.9 LED Luminous Efficiency: <b>130lm/W</b> Operating Voltage: DC(12V 24V)/ AC(100V~277V)/Frequency(50~60Hz) Efficiency: > 90% Effective Beam Angle: 30°/50° Ra) 75 color temperature : 2700K~7000K Light Source Life-span: > 50000Hrs Protection class IP65 Net weight (Unit: kg): 13kg	15 134,40 Kč
<p><b>HB-4M</b></p> 	HB-4M 200W(AC/DC)		27 864,00 Kč
	HB-4M 220W(AC/DC)	Power : 200W-280W Power Factor (PF) : > 0.9 LED Luminous Efficiency: <b>130lm/W</b> Operating Voltage: DC(12V 24V)/ AC(100V~277V)/Frequency(50~60Hz) Efficiency: > 90% Effective Beam Angle: 30°/50° Ra) 75 color temperature : 2700K~7000K Light Source Life-span: > 50000Hrs Protection class IP65 Net weight (Unit: kg): 27kg	28 332,00 Kč
	HB-4M 240W(AC/DC)		28 893,60 Kč
	HB-4M 260W(AC/DC)		29 502,00 Kč
	HB-4M 280W(AC/DC)		30 016,80 Kč
<p><b>RT470FS-S</b></p> 	RT470FS-S140W(AC/DC)	Power : 140w--200w Power Factor (PF) : > 0.9 LED Luminous Efficiency: <b>130lm/W</b> Operating Voltage: DC(12V 24V)/ AC(100V~277V)/Frequency(50~60Hz) Efficiency: > 90% Effective Beam Angle: 30° /50° Ra) 75 color temperature : 2700K~7000K Light Source Life-span: > 50000Hrs Protection class IP65 Net weight (Unit: kg): 14kg	13 917,60 Kč
	RT470FS-S160W(AC/DC)		14 385,60 Kč
	RT470FS-S180W(AC/DC)		14 572,80 Kč
	RT470FS-S200W(AC/DC)		14 760,00 Kč
<p><b>RT410FL-S</b></p> 	RT410FL-S140W(AC/DC)	Power : 140w--200w Power Factor (PF) : > 0.9 LED Luminous Efficiency: <b>130lm/W</b> Operating Voltage: DC(12V 24V)/ AC(100V~277V)/Frequency(50~60Hz) Efficiency: > 90% Effective Beam Angle: 30° /50°/80-40/ 110-60 Ra) 75 color temperature : 2700K~7000K Light Source Life-span: > 50000Hrs Protection class IP65 Net weight (Unit: kg): 14kg	16 164,00 Kč
	RT410FL-S160W(AC/DC)		16 912,80 Kč
	RT410FL-S180W(AC/DC)		17 380,80 Kč
	RT410FL-S200W(AC/DC)		18 036,00 Kč


Svítlidla pro  
nasvícení  
objektů



<p><b>RT660ST-S</b></p> 	RT660ST-S 200W(AC/DC)	Power : 200w--400w Power Factor (PF) : > 0.9 LED Luminous Efficiency: <b>130lm/W</b>	23 184,00 Kč
	RT660ST-S 240W(AC/DC)	Operating Voltage: DC(12V 24V)/ AC(100V~277V)/Frequency(50~60Hz)	24 120,00 Kč
	RT660ST-S 280W(AC/DC)	Efficiency: > 90% Effective Beam Angle: 20° / 30° / 40°/100 Ra) 75	25 056,00 Kč
	RT660ST-S 320W(AC/DC)	color temperature : 2700K~7000K Light Source Life-span: > 50000Hrs	26 460,00 Kč
	RT660ST-S 360W(AC/DC)	Protection class IP65 Net weight (Unit: kg): 20kg	27 396,00 Kč
	RT660ST-S 400W(AC/DC)		28 332,00 Kč
<p><b>RT390FL</b></p> 	New RT390FL50W/(AC/DC)	Power : 50w--80w Power Factor (PF) : > 0.9 LED Luminous Efficiency: <b>130lm/W</b>	8 442,00 Kč
	New RT390FL60W/(AC/DC)	Operating Voltage: DC(12V 24V)/ AC(100V~277V)/Frequency(50~60Hz)	8 535,60 Kč
	New RT390FL70W/(AC/DC)	Efficiency: > 90% Effective Beam Angle: 30°/50°/140° Ra) 75	8 676,00 Kč
	New RT390FL80W/(AC/DC)	color temperature : 2700K~7000K Light Source Life-span: > 50000Hrs Protection class IP65 Net weight (Unit: kg): 7.4kg	9 003,60 Kč
<p><b>RT590FL-S</b></p> 	New RT590FL-S100W/(AC/DC)	Power : 100w--180w Power Factor (PF) : > 0.9 LED Luminous Efficiency: <b>130lm/W</b>	13 168,80 Kč
	New RT590FL-S120W/(AC/DC)	Operating Voltage: DC(12V 24V)/ AC(100V~277V)/Frequency(50~60Hz)	13 636,80 Kč
	New RT590FL-S140W/(AC/DC)	Efficiency: > 90% Effective Beam Angle: 30° /50°/140° Ra) 75	13 824,00 Kč
	New RT590FL-S160W/(AC/DC)	color temperature : 2700K~7000K Light Source Life-span: > 50000Hrs	14 526,00 Kč
	New RT590FL-S180W/(AC/DC)	Protection class IP65 Net weight (Unit: kg): 12.8kg	15 134,40 Kč

Společnost LED-LUMIN s.r.o. si vyhrazuje právo na změnu cen.

**Reflektory pro čerpací stanice**

Type		Model	Specification	Cena bez DPH
<b>Reflektory pro čerpací stanice</b>		RT330HB60W	Power : 60w--110w Power Factor (PF) : > 0.9 LED Luminous Efficiency: 130lm/W Operating Voltage: DC(12V 24V)/ AC(100V~277V)/Frequency(50~60Hz) Efficiency: > 90% Effective Beam Angle: 30° /50°/80°/140 Ra > 75 color temperature : 2700K~7000K Light Source Life-span: > 50000Hrs Protection class IP65 Net weight (Unit: kg): 6kg	7 084,80 Kč
		RT330HB80W		7 506,00 Kč
		RT330HB100W		7 880,40 Kč
		RT330HB110W		8 020,80 Kč

Společnost LED-LUMIN s.r.o. si vyhrazuje právo na změnu cen.